

Information contained on this Product Information Data Sheet is to the best of our knowledge accurate and reliable. However, no guarantee is given nor intended as conditions of handling and use of this product are beyond our control.

# GEMINI SATIN

## SATIN FLOOR SEALER FINISH

TDWE57-1-1101

DESCRIPTION: -

GEMINI SATIN is a blend of acrylic polymers that provides a durable satin finish for sealed timber, vinyl and linoleum floors.

PHYSICAL PROPERTIES	
Appearance	Opaque white liquid
Odour	Acrylic polymer
pH	8.5 - 9.5
Specific Gravity	1.018 ± 0.005
Percentage Volatiles	84.5 – 85.5%
Coverage	40 - 80 m <sup>2</sup> / litre (Typical)

DIRECTIONS FOR USE: -

**New Floors:** Sealed timber floors should be left between 5 – 7 days before application to ensure all solvent has evaporated.

**Old Floors:** The floor surface should be initially prepared by stripping clean any traces of wax or old polish using ALL PURPOSE STRIPPING EMULSION ensuring thorough removal of all slurry.

**Application:** Apply 3 coats of GEMINI SATIN using a clean lambswool applicator, cotton string mop or fringe mop, allowing sufficient drying time between coats. Wash applicator in water after use. In heavy traffic areas 1 or 2 extra coats should be applied to provide extra durability.

The use of matting is recommended at entrances to prevent the transfer of grit that may scratch the floor.

TDGLA 001

**PEERLESS EMULSION PRODUCTS PTY. LTD. A.C.N. 004 315 619**

Head Office: 173 Grange Road, Fairfield, Victoria, Australia, 3078. TEL: (03) 9499 3161 FAX: (03) 9497 4456.

N.S.W. (02) 9674 3000 QLD. 1 800 001 280 W.A. (08) 9362 1800 S.A. (08) 8352 4077 TAS. (03) 6234 4694 N.T. (08) 8984 3219

Ballarat (03) 5331 3688 Kalgoorlie (08) 9021 4421