

Information contained on this Product Information Data Sheet is to the best of our knowledge accurate and reliable. However, no guarantee is given nor intended as conditions of handling and use of this product are beyond our control.

# GEMINI TIMBER

## TIMBER FLOOR POLISH

TDWT47-1-0101

### DESCRIPTION: -

Gemini Timber is a blend of acrylic polymers which provide a durable protective coating to sealed timber floor surfaces which is easily repaired and has a deep gloss. Gemini Timber is easy to apply and quick drying and can be buffed to a high gloss if required. Provides protection and enhanced appearance over most timber seal finishes.

### PHYSICAL PROPERTIES

|                      |  |
|----------------------|--|
| Appearance           | Opaque white Liquid                      |
| Odour                | Acrylic polymer                          |
| pH                   | 8.5 - 9.5                                |
| Specific Gravity     | 1.032 ± 0.005                            |
| Percentage Volatiles | 76.5 – 77.5%                             |
| Coverage             | 40 - 80 m <sup>2</sup> / litre (Typical) |

### DIRECTIONS FOR USE: -

New floors: Allow 5 – 7 days after the timber seal has dried before applying 3 even coats of Gemini Timber using a clean fine string cotton mop or lambs wool applicator. Ensure previous coat is dry before applying next coat, 30 minutes drying time between coats is normal.

Old floors: Do not use on floors which have been waxed – Remove all traces of wax or old polish with Peerless All Purpose Stripping Emulsion. Rinse floor with clean water before applying Gemini Timber.

TDGLA 001

### PEERLESS EMULSION PRODUCTS PTY. LTD. A.C.N. 004 315 619

Head Office: 173 Grange Road, Fairfield, Victoria, Australia, 3078. TEL: (03) 9499 3161 FAX: (03) 9497 4456.  
 N.S.W. (02) 9674 3000 QLD. (07) 3260 1377 W.A. (08) 9362 1800 S.A. (08) 8352 4077 TAS. (03) 6234 4694 N.T. (08) 8984 3219  
 Ballarat (03) 5331 3688 Kalgoorlie (08) 9021 4421