

Information contained on this Product Information Data Sheet is to the best of our knowledge accurate and reliable. However, no guarantee is given nor intended as conditions of handling and use of this product are beyond our control.

# SURFACE SEAL

## TIMBER & CORK SEAL

TDSE02-1-1100

DESCRIPTION: -

SURFACE SEAL is a combination of penetrating oils and synthetic resins formulated to produce a tough, durable, semi-permanent seal for use on timber, cork, parquetry and composite flooring. SURFACE SEAL dries to a tough durable film that is unaffected by water, dilute acids and alkalis, alcohol or oil. Surface Seal prevents timber floors from drying out and splintering and produces a rich finish that enhances and retains the original natural colours of the timber. On floors not exclusively used for sport, the use of a polish during periodic maintenance will help extend the period between seal recoating.

PHYSICAL PROPERTIES	
Appearance	Slightly viscous tan liquid
Odour	Mineral solvent
Specific Gravity	0.876 ± 0.005
Percentage Volatiles	69.0 – 71.0%
Solubility in Water	Insoluble
Coverage	12 – 16 m <sup>2</sup> /litre (typical)

DIRECTIONS FOR USE: -

**New Untreated Surfaces -** Apply Peerless Fast Dry Penetrating Seal in accordance with label directions, observe cutback procedure and preparation details for subsequent coats of Peerless Seals. Apply Surface Seal with a lambswool applicator, working across the grain and finishing with the grain of the timber.

Provide adequate ventilation during application; avoid puddling of excess seal and work away from sealed area. To provide optimum film, thickness, protection and aesthetic appeal, two coats of Surface Seal is recommended. The second coat within 24 hours of the first drying.

**Aged Floors -** Prior to application of Surface Seal the Floor must be pre-cleaned with Peerless "Timber Preclean", or if polish, sealer finish or wax has been applied, stripped with All Purpose Stripping Emulsion, rinsed with clean water and allowed to dry. When dry cut the floor back with sand screen discs or sandpaper (100 - 120 grit). Sweep or vacuum all dust and "Tack Rag" if necessary. Apply two coats of Surface Seal using a lambswool applicator, applying across the grain and levelling with the grain of the timber. Leave 6 - 8 hours or preferably overnight between coats. For more detailed information, consult the "Peerless Program for Timber Floors" or "Peerless Program for Multi -Purpose Floors."

TDGLA 001

**PEERLESS EMULSION PRODUCTS PTY. LTD. A.C.N. 004 315 619**

Head Office: 173 Grange Road, Fairfield, Victoria, Australia, 3078. TEL: (03) 9499 3161 FAX: (03) 9497 4456.  
 N.S.W. (02) 9674 3000 QLD. (07) 3260 1377 W.A. (08) 9362 1800 S.A. (08) 8352 4077 TAS. (03) 6234 4694 N.T. (08) 8984 3219  
 Ballarat (03) 5331 3688 Kalgoorlie (08) 9021 4421