

Information contained on this Product Information Data Sheet is to the best of our knowledge accurate and reliable. However, no guarantee is given nor intended as conditions of handling and use of this product are beyond our control.

TUNG OIL SEAL

TIMBER & PARQUETRY SEAL

TDSE10-1-0101

DESCRIPTION: -

TUNG OIL SEAL is based on natural Tung oil. Designed as a deep penetrating floor seal that produces a tough, durable semi-permanent surface coating on internal timber and parquet floors.

TUNG OIL SEAL dries to a tough durable film that prevents timber floors from drying out and splintering and produces a rich protective finish that retains and enhances the original natural timber colours.

PHYSICAL PROPERTIES	
Appearance	Thin tan liquid
Odour	Mineral solvent
Specific Gravity	0.890 ± 0.005
Percentage Volatiles	65.0%
Solubility in Water	Insoluble
Coverage	8 – 12 m ² / litre (typical)

DIRECTIONS FOR USE: -

New Untreated Surfaces – Apply Peerless **Tung Oil Seal** in accordance with label directions, observe cutback procedure and preparation details for subsequent coats of **Tung Oil Seal**. Apply **Tung Oil Seal** with a lambswool applicator, working across the grain and finishing with the grain of the timber. Provide adequate ventilation during application, avoid puddling of excess seal and work away from the sealed area. To provide optimum film, thickness, protection and aesthetic appeal, two coats of **Tung Oil Seal** is recommended. The second coat within 24 hours of the first drying. A third coat may be required on more porous floors.

Aged Floors – Prior to application of **Tung Oil Seal** the floor must be pre-cleaned with Peerless **Timber Preclean**, or if polish, sealer finish or wax has been applied, strip with All Purpose Stripping Emulsion, rinse with clean water and allowed to dry. When dry cut back the floor with a sand screen discs or sandpaper (100 grit). Sweep or vacuum all dust and “tack Rag” if necessary. Apply two coats of **Tung Oil Seal** using a lambswool applicator, applying across the grain and levelling with the grain of the timber. Leave 6 – 8 hours or preferably overnight between coats.

TDGLA 001

PEERLESS EMULSION PRODUCTS PTY. LTD. A.C.N. 004 315 619

Head Office: 173 Grange Road, Fairfield, Victoria, Australia, 3078. TEL: (03) 9499 3161 FAX: (03) 9497 4456.
 N.S.W. (02) 9674 3000 QLD. (07) 3260 1377 W.A. (08) 9362 1800 S.A. (08) 8352 4077 TAS. (03) 6234 4694 N.T. (08) 8984 3219
 Ballarat (03) 5331 3688 Kalgoorlie (08) 9021 4421